## **FENCING**

ITEM	SIZE	DESCRIPTION	MATERIAL	FIXING	ALSO AVAILABLE
MORTICE HOLDER	200x62x62mm	Used for original fixing or repair of wooden arris rails into pre-morticed concrete posts.	2mm pre- galvanised mild steel to BS EN 10142:1991 Z275	Use woodscrews or galv nails in all available fixing holes.	N/A
HANDED ARRIS RAIL BRACKETS	62x62x100	Drop-In type bracket for securing wooden arris rails to wooden posts and fencing. Sold in left and right handed pairs.	2mm pre- galvanised mild steel to BS EN 10142:1991 Z275	Use woodscrews or galv nails and coach screws in all available fixing holes.	N/A
PANEL CLIP	44, 46, 48 and 50mm	Used to hold wooden panels to wooden posts.	1.5mm pre- galvanised mild steel to BS EN 10142:1991 Z275	Fix to posts using woodscrews or galv nails. Slot panels in and nail or screw to fix.	N/A
TRELLIS CLIP	35 and 38mm	Used to secure wooden trellis to wooden posts above the fence panels.	1.5mm pre- galvanised mild steel to BS EN 10142:1991 Z275	Fix to posts using woodscrews or galv nails. Slot trellis panels in and nail or screw to fix.	N/A
GRAVEL BOARD BRACKET	150x50mm and 250x50mm	Secures a concrete gravel board between wooden posts.	1.5mm pre- galvanised mild steel to BS EN 10142:1991 Z275	Fix to posts using woodscrews or galv nails and slide gravel boards in.	Available with or without bottom retaining lip
TIMBER GRAVEL BOARD BRACKET	150x25mm	Secures a wooden gravel board between wooden posts.	1.5mm pre- galvanised mild steel to BS EN 10142:1991 Z275	Fix to posts using woodscrews or galv nails, slide in gravel board and fix with nails or screws.	N/A
2 PIN CLEAT	150mm	For securing a concrete gravel board to a pre-holed concrete post.	5mm hot dip galv. Mild steel	Slot the pins of the cleat into the holes in the post and secure the gravel board with bolts.	Extended 2 Pin Cleat for double gravel boards
FLAT STRAPS	500x95mm	Flat straps for forming into birdsmouth straps on site.	0.7mm pre- galvanised mild steel to BS EN 100142:1991 Z275	Position on post and rail type fencing and bend into shape. Secure with nails.	Once bent, 3 bend and 5 bend straps